



型號 Type	外形尺寸(mm) Dimensions						額定負荷(kN) Rated load		極限轉速 Limiting		重量 (Kg) Mass
	d	D	H	B	C	S	Cr	Cor	脂潤滑	油潤滑	
29412E	60	130	42	16	21	38	394	1050	1800	2600	2.6
29413E	65	140	45	17	22	42	447	1214	1700	2400	3.2
29414E	70	150	48	18	24	44	506	1393	1600	2200	3.9
29415E	75	160	51	19	25	47	564	1573	1600	2200	4.7
29416E	80	170	54	20	26	50	628	1752	1500	2000	5.68
29417E	85	180	58	21	28	54	711	2097	1300	1800	6.75
29418E	90	190	60	22	29	56	729	2000	1300	1800	7.78
29420E	100	210	67	25	33	62	913	2636	1100	1600	11
29422E	110	230	73	26	35	69	1110	3220	950	1400	14.3
29424E	120	250	78	30	38	74	1240	3650	900	1300	17.83
29426E	130	270	85	31	41	81	1490	4640	850	1200	22.4
29428E	140	280	85	31	41	86	1520	4660	850	1200	23.1
29430E	150	300	90	32	44	92	1720	5570	800	1100	28
29432E	160	320	95	34	45	99	1870	5750	750	1000	33.5
29434E	170	340	103	37	50	104	2170	6850	700	950	41
29436E	180	360	109	39	52	110	2340	7430	670	900	48.5
29438E	190	380	115	43	56	117	2572	8300	630	850	58.9
29440E	200	400	122	44	59	122	3010	10170	600	800	72
29444E	220	420	122	44	59	132	3070	10600	560	750	75
29448E	240	440	122	43	59	142	3090	10600	560	750	79.1
29452E	260	480	132	50	65	154	3590	12550	500	670	100.7
29456E	280	520	145	52	68	166	4128	13990	480	630	124.8
29460E	300	540	145	53	71	175	4340	15700	450	600	131
29464E	320	580	155	56	75	191	5060	18500	430	560	175
29468E	340	620	170	61	78	201	5650	20000	380	500	203.7
29472E	360	640	170	62	82	210	5840	21500		500	224.5
29476E	380	670	175	65	85	230	6400	24500		480	249.4
29480E	400	710	185	68	89	236	6730	25740		450	310
29484E	420	730	185	67	89	244	6890	26520		430	362.2
29488E	440	780	206	74	100	260	8120	30810		380	477.2